

GeneralAire® Models DH75 & DH100 Wi-Fi Dehumidifiers

Wi-Fi & Touch Screen Control

Spec Sheet

Installs Quickly & Easily

DH75 (GFI #5333) & DH100 (GFI #5334)

Capacity	Up To 75 Pints Per 24 Hours @ 80°F / 27°C - 60% RH	Up To 100 Pints Per 24 Hours @ 80°F / 27°C - 60% RH
Weight (Pounds)	58	65
Dimensions (Inches)	12.75 H x 12.6 W x 21 D	15.75 H x 12.6 W x 21 D
Home Size (Square Feet)	3,800	5,200
Control	Wi-Fi and Touch Screen	
Power Supply	120VAC, 60Hz	120VAC, 60Hz
Energy Factor (liters/kwh)	2.0	1.86
Current Draw (Amps)	6.2	8.8
Air Flow (CFM)	180	220
Inlet Air Operating Temperature	50°F - 90°F / 10°C - 32°C	
Control Board Display Temperature	-4°F - 158°F operating / -22°F - 176°F storage -20°C - 70°C operating / -30°C - 80°C storage	
Filter Dimensions (Inches)	MERV 11 Pleated Filter GFI #7143 10 x 12 x 1 Replace Every 6 Months	MERV 11 Pleated Filter GFI #7144 12 x 12 x 1 Replace Every 6 Months
Cabinet Insulation	Foil-faced fiberglass 1/2" thick & closed cell foam	
Duct Connections (Inches)	8 Diameter (Inlet & Outlet)	10 Diameter (Inlet & Outlet)
Drain Pan	Heavy Duty, Injection Molded	
Noise (dB)	Less Than 55 (unducted)	
Warranty (Years)	Five	
Typical Installation	Crawl Space, Attic, Basement; Ducted or Unducted	
In The Box	Dehumidifier, Installation Manual, Power Cord, MERV 11 Filter, Duct Mount Collars	

Accessories

- Hanging kits (GFI #6560)
- Dehumidistat DHX3 (GFI #7175)
- Bracket to Hang Pump (GFI #7147)



Tested to ANSI/UL STD 474, and to Can/CSA Std C22.2 No. 92-197 and applicable sections of ANSI/UL STD 1995.

Download the GeneralAire® WiFi APP
(Apple APP Store or Google Play)



Designed & Assembled
in Michigan, USA



General Filters
Inc.

43800 Grand River Avenue Novi, Michigan 48375 Toll Free: (866) 476-5101 www.generalaire.com



GeneralAire® Models DH75 & DH100 Wi-Fi Dehumidifiers


Wi-Fi & Touch Screen Control

Spec Sheet

Installs Quickly & Easily

DH75 & DH100 Features

- Remove up to 100 pints per day.
- Wi-Fi and touch screen control for user convenience.
- Fan-only Function. Set for 10, 20, or 30 minutes per hour.
- Filter hour indicator (replace MERV 11 filter annually).
- Low temperature shutoff.
- Comfortable handles integrated into both the box and the unit for ease of transport and installation.
- Small footprint and light weight enhances installation options.
- Adjustable feet for leveling.
- Safety grates.
- Duct mount collars (included).
- Quarter turn screw door release for easy MERV 11 filter replacement.
- Help buttons take you to dehumidifier help topics on www.generalfilters.com.
- Humidity sensor offset (+/- 5%) for calibration to another humidity measuring device in the home.
- Low voltage connection for remote dehumidistat or water leak detection device.
- APP attempts to reconnect should Wi-Fi be lost, until connection is restored.
- Dewpoint lockout setpoint.



See installation manual for instructions on how to download and use the GeneralAire® APP. Or go to www.generalfilters.com, dehumidifier help topics.



Maintenance

Maintenance of your new GeneralAire® Dehumidifier is minimal:

- Replace the MERV 11 pleated filter once every 6 months.

**Do not operate your dehumidifier without a filter.

Product Support

- Installation Manual
- Home Owner Brochure
- Competitive Comparison
- www.GeneralFilters.com Help Topics
- Tech Support (866) 476-5101

GFI #7143
for DH75



GFI #7144
for DH100



General Filters
Inc.

43800 Grand River Avenue Novi, Michigan 48375 Toll Free: (866) 476-5101 www.generalaire.com